

POOLMANAGER

BAYROL POOLMANAGER

Specifications	
Volt	230
Max power consumption	10 amp.
Hz	50 - 60Hz
IP	65
Measuring method	pH & Chlorine (mv) + temp. (Select model)
Measuring method	pH & Bromine (mv) + temp. (Select model)
Measuring method	pH & Oxygen + temp in comp. (Select model)
Handling	Touch screen.
Display	5,7" LCD touch screen with blue background light
Pump dosing method / functions	Auto / off / manual. Dosing rate 0 - 100%
pH value range	0,00 - 9,00 pH
Chlorine value range	(redox) 0-999 mV. D+ / D-
Oxygen value range	Dose by amount or day-program
Temperature value range	0,0 - 99,9°C
Flockmatic	Out put for extern flock pump
Alarm	All channals have low / high alarms and dosing time alarm
Alarm for level control	All channals have level alarm. (BNC)
Flow celle	Clear flow celle with blue background light
Flow sensor	Stop / go for dosing
Flow filter	Yes
Climatic limitation	0 - 45°C
Chemical pumps:	
Pumps	Both chemical pumps are built-in. IP40
Pump capacity	0,9L/h for pH and redox
Pump capacity	6,0L/h for BayroSoft
Communication:	
Event Log	Records up to 100 events with date and time
Option for communication	PoolConnect GSM module for automatically informations
Option for extra / extern reading	PC-Communication via an RS-485 interface logging
Display languages	8 diffrent languages inc. Danish
Dimensions	630mm. x 530mm. x 180mm (WxHxD)

POOLMANAGER

BAYROL POOLMANAGER

