

NORDIK SAND FILTERS - NOZZLE

Kripsol Nordik sand filters are multilayer polyester laminated filters.

Kripsol Nordik sand filters are made on plate with nozzles.

Kripsol Nordik sand filters has a oval man hole lid 400x300mm.

Kripsol Nordik sand filters are manufacture according DIN norms 19605 & 19643.

Testing pressure 3,75 bar. (Kg/cm²)

Max working pressure 2,5 bar. (Kg/cm²)

Best working pressure 0,5 - 2,0 bar. (Kg/cm²)

Maximum water temperature 40°C

Specification/D in mm	1050	1200	1400	1600	1800	2000
Filter areal m ²	0,86	1,13	1,54	2,01	2,54	3,14
Filtration bed depth in m	1,2	1,2	1,2	1,2	1,2	1,2
Water flow at 20/40m ³ /h/m ²	16,5 / 33	22 / 44	30,5 / 61	40 / 80	50 / 100	62,5 / 125
Connection flange. D pipe mm	110	125	140	160	200	225
Filter netto weight i Kg	190	300	376	449	528	647
Sand gravel kg. Size 3,0 - 6,0 mm	125	175	225	300	400	475
Sand gravel kg. Size 1,4 - 2,5 mm	125	175	225	300	400	475
Sand gravel kg. Size 0,4 - 0,8 mm	1200	1700	2325	3025	3825	4725